

[별표 4] (제5조제2호 관련)

나사측정용플럭게이지

(단위 : 밀리미터)

항목 호칭 분류		유효치름	바깥치름	피치허용차	산의반각 허용차	게이지 길이
25	통과 (공용)	33.167+0.010 +0	35.230+0.018 +0	3.175±0.010	30°±5'	28.5
	정지 (검사용만)	33.167+0.282 +0.272	34.444(표준치)	3.175±0.010	30°±5'	21.0
40	통과 (공용)	48.971+0.015 +0.005	50.8+0.020 +0	2.822±0.010	30°±5'	25.4
	정지 (검사용만)	48.971+0.404 +0.394	50.051(표준치)	2.282±0.010	30°±5'	18.7
65	통과 (공용)	75.588+0.019 +0.006	77.788+0.023 +0	3.387±0.010	30°±5'	21.2
	정지 (검사용만)	75.588+0.454 +0.441	76.750(표준치)	3.387±0.010	30°±5'	15.5
75	통과 (공용)	89.677+0.013 +0	92.428+0.023 +0	4.232±0.010	30°±5'	29.6
	정지 (검사용만)	89.677+0.457 +0.445	90.128(표준치)	4.232±0.010	30°±5'	21.2
90	통과 (공용)	105.552+0.015 +0	108.303+0.033 +0	4.232±0.010	30°±5'	29.6
	정지 (검사용만)	105.552+0.457 +0.442	106.002(표준치)	4.232±0.010	30°±5'	21.2
100	통과 (공용)	123.787+0.015 +0	127.912+0.038 +0	6.350±0.010	30°±5'	32
	정지 (검사용만)	123.787+0.635 +0.620	124.415(표준치)	6.350±0.010	30°±5'	44.5
115	통과 (공용)	142.837+0.015 +0	146.962+0.038 +0	6.350±0.010	30°±5'	32
	정지 (검사용만)	142.837+0.635 +0.620	143.465(표준치)	6.350±0.010	30°±5'	44.5
125	통과 (공용)	155.514+0.015 +0	159.639+0.038 +0	6.350±0.010	30°±5'	32
	정지 (검사용만)	155.514+0.635 +0.620	156.144(표준치)	6.350±0.010	30°±5'	44.5
150	통과 (공용)	174.945+0.635 +0	179.070+0.038 +0	6.350±0.010	30°±5'	32
	정지 (검사용만)	174.945+0.635 +0.620	175.573(표준치)	6.350±0.010	30°±5'	44.5