

[별표 3] (제4조제1항제2호 관련) <개정 2024.8.28.>

나사측정용플럭게이지

(단위 : mm)

호칭	분류	항목	유효치름	바깥치름	피치허용차	산의반각 허용차	게이지 길이
25	통과 (공용)		33.167+0.010 +0	35.230+0.018 +0	3.175±0.010	30°±5'	28.5
	정지 (검사용만)		33.167+0.282 +0.272	34.444(표준치)	3.175±0.010	30°±5'	21.0
40	통과 (공용)		48.971+0.015 +0.005	50.8+0.020 +0	2.822±0.010	30°±5'	25.4
	정지 (검사용만)		48.971+0.404 +0.394	50.051(표준치)	2.282±0.010	30°±5'	18.7
65	통과 (공용)		75.588+0.019 +0.006	77.788+0.023 +0	3.387±0.010	30°±5'	21.2
	정지 (검사용만)		75.588+0.454 +0.441	76.750(표준치)	3.387±0.010	30°±5'	15.5
75	통과 (공용)		89.677+0.013 +0	92.428+0.023 +0	4.232±0.010	30°±5'	29.6
	정지 (검사용만)		89.677+0.457 +0.445	90.128(표준치)	4.232±0.010	30°±5'	21.2
90	통과 (공용)		105.552+0.015 +0	108.303+0.033 +0	4.232±0.010	30°±5'	29.6
	정지 (검사용만)		105.552+0.457 +0.442	106.002(표준치)	4.232±0.010	30°±5'	21.2
100	통과 (공용)		123.787+0.015 +0	127.912+0.038 +0	6.350±0.010	30°±5'	32
	정지 (검사용만)		123.787+0.635 +0.620	124.415(표준치)	6.350±0.010	30°±5'	44.5
115	통과 (공용)		142.837+0.015 +0	146.962+0.038 +0	6.350±0.010	30°±5'	32
	정지 (검사용만)		142.837+0.635 +0.620	143.465(표준치)	6.350±0.010	30°±5'	44.5
125	통과 (공용)		155.514+0.015 +0	159.639+0.038 +0	6.350±0.010	30°±5'	32
	정지 (검사용만)		155.514+0.635 +0.620	156.144(표준치)	6.350±0.010	30°±5'	44.5
150	통과 (공용)		174.945+0.635 +0	179.070+0.038 +0	6.350±0.010	30°±5'	32
	정지 (검사용만)		174.945+0.635 +0.620	175.573(표준치)	6.350±0.010	30°±5'	44.5